



SAFETY DATA SHEET

Page 1 of 6
POC-9015

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	PETRA WASHER FLUID CONCENTRATE
1.2	Chemical Name:	Petroleum Distillates
1.3	Synonyms:	9015
1.4	Trade Names:	Petra Washer Fluid Concentrate
1.5	Product Use:	Fuel Additive
1.6	Distributor's Name:	Petra Oil NZ
1.7	Distributor's Address:	50 Jacobs Lane, Ngaruawahia 3792, New Zealand
1.8	Emergency Phone:	NZ NATIONAL POISONS CENTRE (0800) 764 766
1.9	Business Phone / Fax:	Tel: +64 (21) 771 703

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of WHSR and ADG Code (Australia). DANGER! FLAMMABLE LIQUID AND VAPOR. FATAL IF SWALLOWED. CAUSES SERIOUS EYE DAMAGE. MAY DAMAGE FERTILITY OR THE UNBORN CHILD. CAUSES DAMAGE TO ORGANS. Classification: Flam. Liq. 2, Acute Tox. 1 (oral), Eye Dam. 1, Repr. 1B, STOT SE 1	
2.2	Label Elements:	<u>Hazard Statements</u> (H): H226 - Flammable liquid and vapor. H300 - Fatal if swallowed. H318 - Causes serious eye damage. H360 - May damage fertility or the unborn child. H370 - Causes damage to organs. <u>Precautionary Statements</u> (P): P201 - Obtain special instructions. P202 - Do not handle until all safety precautions have been read and understood. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 - Keep container tightly closed. P240 - Ground/Bond container and receiving equipment. P241 - Use explosion-proof electrical, ventilating, lighting equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P260 - Do not breathe fumes, mist, vapor or spray. P264 - Wash affected areas thoroughly after handling. P270 - Wash hands and exposed skin areas with soap and warm water thoroughly after handling. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P301+P310 - If swallowed: Immediately call a poison control center, doctor/physician. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 - If exposed or concerned: Get medical advice/attention. P310 - Immediately call a POISON CONTROL CENTER or doctor, if you feel unwell. P321 - Specific treatment: See section 4.1 of the Safety Data Sheet. P330 - Rinse mouth. P331 - Do NOT induce vomiting. P362+P364 - Take off contaminated clothing and wash it before reuse. P370+P378 - In case of fire: In case of fire: Use CO ₂ , foam, dry powder or water spray to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool. P405 - Store locked up. P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.	   
2.3	Other Warnings:	In the event of an exposure or medical inquiry involving this product, please contact a physician or local poison control center, who may seek advice from the U.S. manufacturer, and show them this SDS. If medical advice is needed, have product container or label at hand. KEEP OUT OF REACH OF CHILDREN.	

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	RTECS No.	EINECS No.	%	EXPOSURE LIMITS IN AIR (mg/m ³)									OTHER
					ACGIH		NOHSC			OSHA				
					TLV	STEL	ppm	ppm	ppm	PEL	STEL	IDLH		
METHANOL	67-56-1	PC1400000	200-659-6	≥ 85	200	250	ES-TWA (200)	ES-STEL 262	ES-PEAK NF	200	250	6000		
POLYETHYLENE GLYCOL	25322-68-3	NA	500-038-2	≤ 0.1	NA	NA	NF	NF	NF	NA	NA	NA		
NONYL NONOXYNOL-5	9014-93-1	NA	618-488-4	≤ 0.1	NA	NA	NF	NF	NF	NA	NA	NA		
HYDROGEN [4-[4-(DIETHYL-AMINO)-2',4'-DISULPHONATO-BENZHYDRYLIDENE] CYCLO-HEXA-2,5-DIEN-1-YLIDENE] DIETHYLAMMONIUM, SODIUM SALT	129-17-9	NA	204-934-1	≤ 0.1	NA	NA	NF	NF	NF	NA	NA	NA		



SAFETY DATA SHEET

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

4. FIRST AID MEASURES

4.1	First Aid:	<p><u>Ingestion:</u> DO NOT INDUCE VOMITING. Contact Poison Control Center or local emergency telephone number for assistance and instructions. If you feel unwell, seek medical advice (show the label where possible). If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.</p> <p><u>Eyes:</u> If product gets in the eyes, flush eyes thoroughly with copious amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.</p> <p><u>Skin:</u> Remove contaminated clothing and wash affected areas with soap and water. If discomfort persists and/or the skin reaction worsens, contact a physician immediately. Do not wear contaminated clothing until after it has been properly cleaned.</p> <p><u>Inhalation:</u> Remove victim to fresh air at once. Under extreme conditions, if breathing stops, perform artificial respiration. Seek immediate medical attention.</p>												
4.2	Effects of Exposure:	<p><u>Ingestion:</u> Irritation to the gastrointestinal tract. This material can enter the lungs during swallowing or vomiting and cause lung damage.</p> <p><u>Eyes:</u> Irritation upon direct contact. Symptoms may include stinging, tearing, redness and swelling.</p> <p><u>Skin:</u> Mildly irritating. Prolonged or repeated skin contact can result in defatting, drying of the skin with symptoms of redness, stinging.</p> <p><u>Inhalation:</u> Harmful if inhaled. May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation. May be fatal if swallowed and enters airways.</p>												
4.3	Symptoms of Overexposure:	<p><u>Ingestion:</u> Nausea, intestinal discomfort, vomiting and/or diarrhea.</p> <p><u>Eyes:</u> Overexposure in eyes may cause redness, itching and watering.</p> <p><u>Skin:</u> Symptoms of skin overexposure may include redness, itching, and irritation of affected areas. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some individuals.</p> <p><u>Inhalation:</u> May cause respiratory irritation. Irritation of the nasal mucous membranes. Irritation of the respiratory tract. Danger of serious damage to health by prolonged exposure through inhalation.</p>												
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.												
4.5	Chronic Health Effects:	Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention. Suspected of damaging fertility or the unborn child. Causes damage to organs. Repeated exposure to this material can result in absorption through skin causing significant health hazard.												
4.6	Target Organs:	Eyes, Skin, Lungs												
4.7	Medical Conditions Aggravated by Exposure:	Pre-existing skin, eye, or respiratory disorders.												
		<table border="1"> <tr> <td>HEALTH</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td>3</td> </tr> <tr> <td>PHYSICAL HAZARDS</td> <td>1</td> </tr> <tr> <td>PROTECTIVE EQUIPMENT</td> <td>B</td> </tr> <tr> <td>EYES</td> <td>SKIN</td> </tr> <tr> <td>LUNGS</td> <td></td> </tr> </table>	HEALTH	1	FLAMMABILITY	3	PHYSICAL HAZARDS	1	PROTECTIVE EQUIPMENT	B	EYES	SKIN	LUNGS	
HEALTH	1													
FLAMMABILITY	3													
PHYSICAL HAZARDS	1													
PROTECTIVE EQUIPMENT	B													
EYES	SKIN													
LUNGS														

5. FIREFIGHTING MEASURES

5.1	Fire & Explosion Hazards:	DANGER! FLAMMABLE LIQUID AND VAPOR. May form flammable/explosive vapor-air mixture. Keep away from heat, hot surface, sparks, open flames and other ignition sources. No smoking. Use foam, dry powder, carbon dioxide, water spray or sand to extinguish fire. Do NOT use a heavy water stream. If involved in a fire, this product may decompose at high temperatures to form toxic gases (e.g., CO, CO _x , hydrocarbons). Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container.	
5.2	Extinguishing Methods:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam. Use water spray to cool fire-exposed containers. Water may be ineffective. For large fires, use water spray, fog or alcohol-resistant foam. Do NOT use straight streams of water.	
5.3	Firefighting Procedures:	As with any fire, firefighters should wear appropriate protective equipment including a MSHA/NIOSH approved or equivalent self-contained breathing apparatus (SCBA) and protective clothing. Treat as hot oil. Hazardous decomposition products may be released. Thermal degradation may produce oxides of carbon, and/or nitrogen, hydrocarbons and/or derivatives. Fire should be fought from a safe distance. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personal. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway.	



SAFETY DATA SHEET

Page 3 of 6
POC-9015

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment.</p> <p>For <u>small spills</u> (e.g., < 1 gallon (3.8 L)) wear appropriate personal protective equipment (e.g., goggles, gloves). Maximize ventilation (open doors and windows) and secure all sources of ignition. Remove spilled material with absorbent material and place into appropriate closed container(s) for disposal. Dispose of properly in accordance with local, state and federal regulations. Wash all affected areas and outside of container with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse.</p> <p>For <u>large spills</u> (e.g., ≥ 1 gallon (3.8 L)), deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g., sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Transfer liquid to containers for recovery or disposal and solid diking material to separate containers for proper disposal. Remove contaminated clothing promptly and wash affected skin areas with soap and water. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.</p>
-----	---------	--

7. HANDLING & STORAGE INFORMATION

7.1	Work & Hygiene Practices:	Avoid prolonged contact with the product. Avoid breathing vapors of this product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.
7.2	Storage & Handling:	Keep this material away from heat, sparks and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty container may contain residual amounts of this product; therefore, empty containers should be handled with care. Store containers in a cool, dry location, away from direct sunlight, other light sources, or sources of intense heat. Store away from incompatible materials (See Section 10).
7.3	Special Precautions:	Open containers slowly on a stable surface. Keep container tightly closed when not in use. Empty containers may contain residual amounts of this product; therefore, empty containers should be handled with care.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: ppm (mg/m ³)	ACGIH		NOHSC			OSHA			OTHER	
		TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH		
		CHEMICAL NAME(S)									
		METHANOL		200	250	(200)	262	NF	200	250	6000
8.2	Ventilation & Engineering Controls:	Use general/dilution or local exhaust ventilation as needed to ensure that occupational exposure limits are not exceeded. Do not use in enclosed spaces. When working with large quantities of product, provide adequate ventilation (e.g., local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.									
8.3	Respiratory Protection:	Vaporization or misting is not expected at ambient temperatures. Therefore, the need for respiratory protection is not anticipated under normal use conditions and with adequate ventilation. If elevated airborne concentrations above applicable workplace exposure levels are anticipated, a NIOSH-approved organic vapor respirator equipped with a dust/mist pre-filter should be used. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134).									
8.4	Eye Protection:	Wear protective eyewear (e.g., safety glasses with side-shield) at all times when handling this product. Always use protective eyewear when cleaning spills or leaks. Contact lenses pose a special hazard; soft lenses may absorb and concentrate irritants. Have suitable eye wash water available. Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).									
8.5	Hand Protection:	Use gloves constructed of chemical-resistant materials such as neoprene or heavy nitrile rubber if frequent or prolonged contact is expected. If necessary, refer to U.S. OSHA 29 CFR §1910.138, the appropriate standards of Canada, or the EU member states.									
8.6	Body Protection:	Avoid prolonged and/or repeated skin contact. Use clean and impervious protective clothing (e.g., neoprene or Tyvek®). Protective clothing should include long-sleeves, apron, boots and additional facial protection. If necessary, refer to appropriate standards of Canada, the EU member states, or U.S. OSHA.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Blue liquid.
9.2	Odor:	Characteristic odor. Mild odor. Pleasant odor. Alcohol odor. Commercial/unpurified substance: Irritating/pungent odor.
9.3	Odor Threshold:	2000 - 8800 ppm
9.4	pH:	NA
9.5	Melting Point/Freezing Point:	-98 °C (-144.4 °F)
9.6	Initial Boiling Point/Boiling Range:	65 °C (149 °F)
9.7	Flashpoint:	11 °C (51.8 °F)
9.8	Upper/Lower Flammability Limits:	LEL: 5.5% / UEL: 36%
9.9	Vapor Pressure:	836 mm Hg @ 20 °C
9.10	Vapor Density:	1.0 (Air = 1.0)
9.11	Relative Density:	0.792
9.12	Solubility:	Soluble in water.



SAFETY DATA SHEET

Page 4 of 6
POC-9015

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

9. PHYSICAL & CHEMICAL PROPERTIES

9.13	Partition Coefficient (log P_{ow}):	-0.77
9.14	Autoignition Temperature:	455 °C (851 °F)
9.15	Decomposition Temperature:	NA
9.16	Viscosity:	0.6 mPa-s @ 20 °C
9.17	Other Information:	Evaporation Rate: 4.1 (n-Butyl Acetate=1.0); VOC: > 98%

10. STABILITY & REACTIVITY

10.1	Stability:	Relatively stable under ambient conditions when stored properly. Flammable liquid and vapor. May form flammable/explosive vapor-air mixture.
10.2	Hazardous Decomposition Products:	If exposed to <u>extremely high temperatures</u> , products of thermal decomposition may include irritating vapors and toxic gases (e.g., oxides of carbon & nitrogen).
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid:	Exposure or contact to extreme temperatures, incompatible chemicals, strong light sources, sparks, flame.
10.5	Incompatible Substances:	Strong oxidizers, peroxides or strong acids or alkalis.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product has NOT been tested on animals to obtain toxicology data. Toxicology data, found in scientific literature, is available for some of the components of the product and is presented below. Methanol – LD ₅₀ (oral, rat): 5,628 mg/kg; LD ₅₀ (dermal, rabbit) 15,840 mg/kg; LC ₅₀ (inh, rat, 4h) 64,000 ppm		
11.3	Acute Toxicity:	May be fatal if swallowed and enters airways. May be harmful if swallowed and enters airways. May cause respiratory irritation. Irritation of the nasal mucous membranes and respiratory tract. May cause moderate eye and skin irritation.		
11.4	Chronic Toxicity:	May cause damage to organs through prolonged or repeated exposure.		
11.5	Suspected Carcinogen:	NA		
11.6	Reproductive Toxicity:	This product is not reported to produce reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not reported to cause teratogenic effects in humans.		
	Reproductive Toxicity:	Suspected of damaging fertility or the unborn child.		
11.7	Irritancy of Product:	See Section 4.2		
11.8	Biological Exposure Indices:	NE		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	Analysis for ecological effects has not been conducted on this product. However, if spilled, this product and any contaminated soil or water may be harmful to human, animal, and aquatic life.
12.2	Effects on Plants & Animals:	There are no specific data available for this product. An environmental fate analysis has not been conducted on this specific product.
12.3	Effects on Aquatic Life:	Methanol: LC ₅₀ (Oncorhynchus mykiss, 96h): 19,000 mg/L; LC ₅₀ (Pimephales promelas, 96h): 29,700 mg/L.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Dispose of in accordance with local, state, provincial and federal laws and regulations. Disposal of hazardous waste must be through by a licensed treatment, storage or disposal facility (TSDF).
13.2	Special Considerations:	U.S. EPA RCRA Characteristic Waste (Ignitable): D001, U154

14. TRANSPORTATION INFORMATION

The basic description (ID Number, proper shipping name, hazard class & division, packing group) is shown for each mode of transportation. Additional descriptive information may be required by 49 CFR, IATA/ICAO, IMDG and the CTDGR.

14.1	49 CFR (GND):	UN1230, METHANOL SOLUTION, 3, II (LTD QTY, IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg) – until 12/31/20	
14.2	IATA (AIR):	UN1230, METHANOL SOLUTION, 3 (6.1), II (LTD QTY, IP VOL ≤ 0.5 L, OP VOL ≤ 1.0 L); or ID8000, CONSUMER COMMODITY, 9 (LTD QTY, IP VOL ≤ 0.5 L, OP MASS ≤ 30 kg)	
14.3	IMDG (OCN):	UN1230, METHANOL SOLUTION, 3 (6.1), II (LTD QTY, IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg)	
14.4	TDGR (Canadian GND):	UN1230, METHANOL SOLUTION, 3 (6.1), II (LTD QTY, IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg)	
14.5	ADR/RID (EU):	UN1230, METHANOL SOLUTION, 3 (6.1), II (LTD QTY, IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg) Transport Cat: 2; Tunnel Code: (D/E)	
14.6	SCT (MEXICO):	UN1230, METANOL EN SOLUCION, 3 (6.1), II (LTD QTY, IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg)	
14.7	ADGR (AUS):	UN1230, METHANOL SOLUTION, 3 (6.1), II (LTD QTY, IP VOL ≤ 1.0 L, OP MASS ≤ 30 kg)	



SAFETY DATA SHEET

Page 5 of 6
POC-9015

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product contains <u>Methanol</u> , a substance subject to SARA Title III, Section 313 reporting requirements
15.2	SARA TPQ:	There are no specific Threshold Planning Quantities for the components of this product.
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
15.4	CERCLA Reportable Quantity:	<u>Methanol</u> : 5,000 lbs (2,270 kg)
15.5	Other Federal Requirements:	NA
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS B2, D1B (Flammable Liquid, Toxic Material). 
15.7	State Regulatory Information:	<u>Methanol</u> is listed on the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), and Wisconsin Hazardous Substances List (WI). No other ingredients in this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).
15.8	Other Requirements:	All components are either listed on the U.S. TSCA inventory or are not regulated under TSCA under 40 CFR § 720.30. Listed on AICS (Australian Inventory of Chemical Substances) Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China) Listed on KECI (Korean Existing Chemicals Inventory) New Zealand Inventory of Chemicals (NZIoC) Registration Status: CAS 67-56-1: HSR001186 NZIoC Classification: 3.1C, 6.1D, 6.1E, 6.7A, 6.7B, 6.8B; N.O.S. (Flammable, Toxic [6.1, 6.7]) – HSR002622 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

16. OTHER INFORMATION

16.1	Other Information:	DANGER! FLAMMABLE LIQUID AND VAPOR. FATAL IF SWALLOWED. CAUSES SERIOUS EYE DAMAGE. MAY DAMAGE FERTILITY OR THE UNBORN CHILD. CAUSES DAMAGE TO ORGANS. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground/Bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes, mist, vapor or spray. Wash affected areas thoroughly after handling. Wash hands and exposed skin areas with soap and warm water thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, protective clothing, eye protection, face protection. If swallowed: Immediately call a poison control center, doctor/physician. If on skin: Wash with plenty of soap and water. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a POISON CONTROL CENTER, doctor, if you feel unwell. Get medical advice/attention if you feel unwell. Specific treatment: See section 4.1 of the Safety Data Sheet. Rinse mouth. Do NOT induce vomiting. Take off contaminated clothing and wash it before reuse. In case of fire: Use CO ₂ , foam, dry powder or water spray to extinguish. Store in a well-ventilated place. Keep cool. Store locked up. KEEP OUT OF REACH OF CHILDREN.	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of ShipMate's, Smarter Sorting's & Petra Oil Company's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared for:	Petra Oil Company 50 Jacobs Lane Ngaruawahia 3792, New Zealand Tel: +64 (21) 771 703 Email: agacita@petraoilco.com	
16.5	Prepared by:	Smarter Sorting 2900 E. Cesar Chavez Street Austin, TX 78702 USA Tel: +1 (512) 593-2594 E-mail: support@smartersorting.com https://www.smartersorting.com	



SAFETY DATA SHEET

Page 6 of 6
POC-9015

Prepared to OSHA, ACC, ANSI, WHSR, WHMIS, GHS & EU Standards

SDS Revision: 1.1

SDS Revision Date: 12/14/2019

DEFINITION OF TERMS

A large number of abbreviations and acronyms appear on a SDS. Some of these that are commonly used include the following:

GENERAL INFORMATION:

CAS No.	Chemical Abstract Service Number
RTECS No.	Registry of Toxic Effects of Chemical Substances Number
EINECS No.	European Inventory of Existing Commercial Chemical Substances Number

EXPOSURE LIMITS IN AIR:

ACGIH	American Conference on Governmental Industrial Hygienists
IDLH	Immediately Dangerous to Life and Health
NOHSC	National Occupational Health and Safety Commission (Australia)
OSHA	U.S. Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

FIRST AID MEASURES:

CPR	Cardiopulmonary resuscitation - method in which a person whose heart has stopped receives manual chest compressions and breathing to circulate blood and provide oxygen to the body.
-----	--

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM: HMIS

HEALTH, FLAMMABILITY & REACTIVITY RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard

HEALTH
FLAMMABILITY
PHYSICAL HAZARDS
PERSONAL PROTECTION

PERSONAL PROTECTION RATINGS:

A		G	
B		H	
C		I	
D		J	
E		K	
F		X	Consult your supervisor or SOPs for special handling directions.

Safety Glasses	Splash Goggles	Face Shield & Protective Eyewear	Gloves
Boots	Protective Apron	Protective Clothing & Full Suit	Dust Respirator
Full Face Respirator	Dust & Vapor Half-Mask Respirator	Full Face Respirator	Airline Hood/Mask or SCBA

OTHER STANDARD ABBREVIATIONS:


Carc	Carcinogenic
Irrit	Irritant
NA	Not Available
NR	No Results
ND	Not Determined
NE	Not Established
NF	Not Found
SCBA	Self-Contained Breathing Apparatus
Sens	Sensitization
STOT RE	Specific Target Organ Toxicity – Repeat Exposure
STOT SE	Specific Target Organ Toxicity – Single Exposure

NATIONAL FIRE PROTECTION ASSOCIATION: NFPA

FLAMMABILITY LIMITS IN AIR:	
Autoignition Temperature	Minimum temperature required to initiate combustion in air with no other source of ignition
LEL	Lower Explosive Limit - lowest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source
UEL	Upper Explosive Limit - highest percent of vapor in air, by volume, that will explode or ignite in the presence of an ignition source

HAZARD RATINGS:

0	Minimal Hazard
1	Slight Hazard
2	Moderate Hazard
3	Severe Hazard
4	Extreme Hazard
ACD	Acidic
ALK	Alkaline
COR	Corrosive
W	Use No Water
OX	Oxidizer
TREFOIL	Radioactive



TOXICOLOGICAL INFORMATION:

LD ₅₀	Lethal Dose (solids & liquids) which kills 50% of the exposed animals
LC ₅₀	Lethal concentration (gases) which kills 50% of the exposed animal
ppm	Concentration expressed in parts of material per million parts
TD ₁₀	Lowest dose to cause a symptom
TCLo	Lowest concentration to cause a symptom
TD ₁₀ , LD ₁₀ , & LD ₅₀ or TC, TC ₁₀ , LC ₁₀ , & LC ₅₀	Lowest dose (or concentration) to cause lethal or toxic effects
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
RTECS	Registry of Toxic Effects of Chemical Substances
BCF	Bioconcentration Factor
TL _m	Median threshold limit
log Kow or log Koc	Coefficient of Oil/Water Distribution

REGULATORY INFORMATION:

WHMIS	Canadian Workplace Hazardous Material Information System
DOT	U.S. Department of Transportation
TC	Transport Canada
EPA	U.S. Environmental Protection Agency
DSL	Canadian Domestic Substance List
NDSL	Canadian Non-Domestic Substance List
PSL	Canadian Priority Substances List
TSCA	U.S. Toxic Substance Control Act
EU	European Union (European Union Directive 67/548/EEC)
WGK	Wassergefährdungsklassen (German Water Hazard Class)

WORKPLACE HAZARDOUS MATERIALS IDENTIFICATION (WHMIS) SYSTEM:

Class A	Class B	Class C	Class D1	Class D2	Class D3	Class E	Class F
Compressed	Flammable	Oxidizing	Toxic	Irritation	Infectious	Corrosive	Reactive

CLP/GHS (1272/2008/EC) PICTOGRAMS:

GHS01	GHS02	GHS03	GHS04	GHS05	GHS06	GHS07	GHS08	GHS09
Explosive	Flammable	Oxidizer	Pressurized	Corrosive	Toxic	Harmful Irritating	Health Hazard	Environment